


**PRODUCT TECHNICAL STATEMENT****RECOMMENDED PRODUCT/DESIGN USE**

- **Applications:** Residential
- **Materials:** Steel 0.55mm G300
- **Colours:** Available in pre-painted ColorCote® ZinaCore™, MagnaFlow™ COLORSTEEL® MAXAM™  
Refer to [www.colorcote.co.nz](http://www.colorcote.co.nz) and [www.colorsteel.co.nz](http://www.colorsteel.co.nz)
- **Durability:** All material selections must be compatible with the prevailing environmental conditions and adjacent materials. Areas not naturally exposed to rain will require scheduled maintenance.

**ENVIRONMENTAL PRODUCT DECLARATION**

Dimond Roofing® has been implementing green building principles across the industry for several years now and has developed a fully realised environmental sustainability pathway to reach our goal of reducing our carbon emissions by 30% by 2030. Dimond Roofing® has met the criteria for “Level A” certification for the Global GreenTag™ GreenRate™ ecolabel and as part of Dimond’s Toitū carbonreduce® accreditation, essential Scope 1 & 2 emissions, are being measured as well as voluntarily measuring Scope 3 emissions.

Dimond Roofing® profiles are accredited with Eco Choice Aotearoa when manufactured from COLORSTEEL®. All manufacturing sites have been Audited by NZ Steel.

Dimond Roofing® recycle all steel scrap waste and offcuts which can then be remelted down and reused in other steel-based products. At the end of its useful life as a roofing profile can be recycled back by remelted down.

**NEW ZEALAND BUILDING CODE COMPLIANCE**

When used in accordance with Dimond Roofing installation and maintenance requirements, facilitate with meeting the following provisions of the NZBC:

- **B1 Structure:** Performance clauses B1.3.1, B1.3.2, B1.3.3 (a) (b) (c) (g) (h), B1.3.4 (b) and (d)
- **B2 Durability:** Performance clauses B2.3.1(b) and (c)
- **C3 Fire affecting areas beyond the fire source:** Performance clauses C3.4(a) and C3.9
- **E2 External moisture:** Performance clauses E2.3.1 and E2.3.2
- **F2 Hazardous building materials:** Performance clause F2.3.1
- **G12 Water Supplies:** Performance clauses G12.3.1 and G12.3.2

To comply with the performance clauses of NZBC E2 all cladding to be installed in accordance with:

- Acceptable Solutions NZS E2/AS1 or an Acceptable Alternative Solution
- MZ Metal Roofing Manufacturers Code of Practice
- Dimond Roofing Specification; details available on [www.dimond.co.nz](http://www.dimond.co.nz)

Dimond Roofing is not subject to any warning or ban under section 26 of the Building Act 2004.

**MAINTENANCE**

In general, NZ metal roofing materials exposed to rain washing can be expected to comply with NZBC B2 without manual washing, or replacement of protective finishes.

Areas not directly exposed to rain, such as soffits, wall cladding under eaves, the undersides of gutters, fascia's,

and sheltered areas like garage doors, will require scheduled maintenance.

Refer to ColorCote® Minimum Maintenance Schedule and COLORSTEEL® Maintenance Recommendations Brochure.

Effective cross-sectional area (with 15mm free board)	4840mm <sup>2</sup>	
Flow capacity	65 litres/min	
Minimum recommended fall	1:500	= 2mm in 1m
Minimum downpipe	Circular	80mm

Catchment area per downpipe based on the above flow capacity is given in Table below to determine the Rainfall Intensity to be used.

Rainfall Intensity, I (mm/hr)	50	60	70	80	90	100	120	140	160	180	200
Catchment Area per downpipe Ac (m <sup>2</sup> )	78	65	56	49	43	39	32	28	24	22	19

Rollforming facility: Christchurch

Gutter bracket material                      Internal                      Galvanised                      1.15mm

Recommended maximum spacings: 900mm spacing  
(Refer to Dimond Roofing – The Installer Guide for recommended spacings where snow fall is possible)

Recommended fixings: Screw fastenings to be compatible with substrate and bracket material

Stop ends: Pre-Painted stop ends are available

Note: For Installation of gutters in snowfall areas refer to the section **Gutter brackets in snowfall areas** in the Dimond roofing Installers Guide.

## DESIGN DETAILS

Design details covering residential & commercial are available at [www.dimond.co.nz](http://www.dimond.co.nz) in PDF, DWG & RVT files under each product section.

## ROOF DRAINAGE DESIGN

The objective of roof drainage systems is to maintain a weatherproof building, to minimise the risk of injury or inconvenience due to flooding, and to avoid potential monetary loss and property damage – including to the contents of buildings.

Roof drainage design requires consideration of:

- Type of gutter (external, internal, valley, or roof gutter)
- Rainfall intensity
- Catchment area
- Gutter fall
- Gutter-cross-sectional area and wetted surface area, and
- Outlet and downpipe capacity.

More information is available under 5.3 of NZMRM COP at [www.metalroofing.org.nz](http://www.metalroofing.org.nz)

## PUBLICATIONS

To achieve the product's full potential, it must be designed, installed, and maintained in accordance with Good Trade Practice. For more information, please refer to:

**NZS E2/AS1:** [www.building.govt.nz](http://www.building.govt.nz)

**NZMRM:** New Zealand Metal Roofing and Wall Cladding Code of Practice – [www.metalroofing.org.nz](http://www.metalroofing.org.nz)

**NZMRM:** Installation Guide – Metal Longrun Roofing and Cladding – [www.metalroofing.org.nz](http://www.metalroofing.org.nz)

**RANZ:** How to Guides – [www.ranz.co.nz](http://www.ranz.co.nz)

**Pacific Coil Coaters:** Choose the Right Roof  
[www.colorcote.co.nz](http://www.colorcote.co.nz)

**Pacific Coil Coaters:** Maintenance Schedule  
[www.colorcote.co.nz](http://www.colorcote.co.nz)

**Pacific Coil Coaters:** Environmental Product Declaration  
[www.colorcote.co.nz](http://www.colorcote.co.nz)

**New Zealand Steel:** Environmental Categories, Warranty & Product Maintenance Recommendations Brochure  
[www.colorsteel.co.nz](http://www.colorsteel.co.nz)

**New Zealand Steel:** Maintenance Recommendations Bulletin – [www.colorsteel.co.nz](http://www.colorsteel.co.nz)

**New Zealand Steel:** Installers Guide [www.colorsteel.co.nz](http://www.colorsteel.co.nz)

**BRANZ:** Good Profiled Metal Roofing and Wall Cladding – [www.branz.co.nz](http://www.branz.co.nz)

**MBIE:** Guide to tolerances, materials and workmanship in new residential construction 2015 – [www.mbie.govt.nz](http://www.mbie.govt.nz)

---

### Dimond Roofing, NZBN 9429037626563

**Contacts:** Technical Advice 0800 766 377 • Sales and Supply 0800 346 663

**Website:** <https://www.dimond.co.nz/>

**Email Specification Team:** [roofspec@dimond.co.nz](mailto:roofspec@dimond.co.nz)

**Email Technical Team:** [rooftech@dimond.co.nz](mailto:rooftech@dimond.co.nz)

**Address:** 48 Victoria Street, Onehunga, Auckland 1061

**Place of Manufacture:** Aotearoa New Zealand



**DISCLAIMER:** As part of Dimond Roofing's policy of continuing product and system development, we reserve the right, at any time and without notice, to discontinue or change the products, materials, design advice, features or specifications represented in the technical literature without incurring any liability. The information in this document is issued for general application in New Zealand and should not be treated as a substitute for detailed technical advice in relation to requirements for individual projects in New Zealand or overseas. To the extent permitted by law, Dimond Roofing disclaim any liability for loss or damage incurred using the information in this document and any technical literature issued by Dimond Roofing unless it is covered by a specific warranty agreement. For more detail, please contact the Technical Assistance Team on 0800 766 377. Date of issue: June 2025, Version: V02.300625

## Contact us

**Dimond Roofing®**

Ph. 0800 Roofspec (0800 766 377)  
or 0800 DIMOND

[dimond.co.nz](http://dimond.co.nz)

 **Dimond Roofing®**